RESEARCH ARTICLE OPEN ACCESS

Advances in Nanotechnology for Treating Water and Textile Wastewater: A Comprehensive Review

Jayakrishnan R*, Hrithika R**
*(Assistant Professor, Department of Civil Engineering, Ahalia School of Engineering & Technology, Kerala
Email: jayan1615@gmail.com)
** (B.Tech Student, Department of Civil Engineering, Ahalia School of Engineering & Technology, Kerala
Email: hrithikahrithi10@gmail.com)

--************************--

Abstract

The increasing global water crisis demands innovative solutions, particularly for treating industrial effluents like textile wastewater containing persistent dyes and toxic chemicals. Nanotechnology has emerged as a transformative approach, leveraging unique nanoscale properties to address these challenges more effectively than conventional methods.

Key developments include Nano filtration membranes with molecular precision, photocatalytic TiO_2 nanoparticles for sunlight-driven degradation, and advanced adsorbents like graphene and carbon nanotubes. These technologies demonstrate exceptional removal efficiencies (>90%) for complex pollutants while offering potential energy and cost savings.

However, practical implementation faces hurdles including nanoparticle toxicity concerns, scalability issues, and economic viability. This review critically examines these nanotechnology applications, focusing on textile wastewater treatment, to assess their real-world feasibility and environmental implications. By addressing both the remarkable potential and existing limitations, we aim to guide future research toward sustainable, large-scale water purification solutions.

The analysis highlights how nanotechnology could revolutionize water treatment paradigms, particularly in industries where traditional methods prove inadequate, while emphasizing the need for responsible development to ensure environmental safety.

*Keywords:***Nanotechnology water treatment, Textile wastewater purification, Nano filtration membranes, Photocatalytic degradation (TiO_2), Graphene oxide adsorption**

--************************--

1. Introduction

Water pollution, particularly from industrial sources, is a growing environmental concern worldwide. Among various industries, the textile sector is one of the largest consumers of water and a major contributor to water pollution. The dyeing and finishing processes in textile production release large volumes of wastewater that contain toxic dyes, heavy metals, salts, and other hazardous organic compounds. These effluents are often resistant to biodegradation and can cause severe damage to aquatic ecosystems, soil quality, and human health if left untreated.

Conventional wastewater treatment methods such as coagulation-flocculation, activated sludge, and chemical oxidation have shown limited efficiency in removing complex dye molecules and dissolved pollutants. Moreover, these methods often require high energy input, generate sludge, and involve high operational costs. As environmental regulations become stricter and sustainable solutions become essential, researchers are exploring advanced technologies for efficient and eco-friendly wastewater treatment.

Nanotechnology has emerged as a powerful tool in this field due to its unique properties at the nanoscale. Nanomaterials possess a high surface-area-to-volume ratio, enhanced reactivity, and tunable surface chemistry, making them ideal for treating textile effluents. Materials such as titanium dioxide (TiO_2), carbon nanotubes, graphene oxide, and Nanozero valent iron (nZVI) have shown excellent results in the removal of dyes, heavy metals, and organic contaminants through processes like adsorption, photo catalysis, and Nano filtration.

This paper reviews recent advancements in nanotechnology for textile wastewater treatment, focusing on the types of nanomaterials used, their removal mechanisms, advantages, limitations, and environmental impacts. It also highlights challenges in scaling up these technologies and suggests future directions for safe and effective implementation. In the context of global water scarcity and pollution, nanotechnology offers a promising and sustainable alternative to traditional treatment systems.

2. Textile Dye Effluent: Characteristics and Treatment Challenges

The textile industry is one of the most water-intensive industries globally, with processes such as sizing, desizing, scouring, bleaching, dyeing, printing, and finishing consuming vast quantities of water and chemicals. As a consequence, this sector generates large volumes of wastewater, which is complex in composition and difficult to treat. Textile dye effluent is often highly coloured, turbid, and toxic, and can severely disrupt aquatic life, soil health, and even human well-being if discharged untreated.

2.1 Composition of Textile Effluents

The typical constituents of textile wastewater include:

Synthetic dyes such as azo dyes, anthraquinone dyes, phthalocyanine dyes, and vat dyes, many of which are complex aromatic compounds. Azo dyes, in particular, are the most widely used due to their cost-effectiveness and color variety, but they are also associated with carcinogenic and mutagenic by-products (e.g., aromatic amines) when degraded anaerobically.

Surfactants and salts used in scouring and dye fixation processes. Common salts such as sodium chloride (NaCl) and sodium sulfate (Na_2SO_4) are present in concentrations up to 100 g/L, significantly increasing the conductivity and osmotic pressure of the effluent.

Heavy metals including chromium (Cr), lead (Pb), copper (Cu), and cadmium (Cd) are used in dye formulations and mordants. These metals can bio accumulate in aquatic organisms and cause neurological, renal, and developmental disorders in humans.

Biodegradation-resistant compounds such as alkyl phenol ethoxylates, formaldehyde, and chlorinated organic substances. These pollutants are not readily decomposed by conventional microbial treatment systems, leading to persistent contamination of natural water bodies.

High chemical oxygen demand (COD) and biochemical oxygen demand (BOD) levels, along with extreme pH values, depending on the stage of processing (e.g., highly alkaline effluents from mercerization).

2.2 Challenges in Conventional Treatment

Traditional wastewater treatment systems, including:
Coagulation–flocculation, Activated sludge processes, Adsorption using activated carbon,
Sedimentation and filtration, Oxidation with ozone or chlorine. Have been widely implemented in the textile industry. However, these methods are generally ineffective in completely removing persistent organic dyes, heavy metals, and emerging contaminants.
Key limitations include: Incomplete decolourization: Many dyes are resistant to light, heat, and microbial degradation. Sludge generation: Coagulation and biological processes produce large volumes of secondary sludge, which is difficult to manage and may contain toxic residues. High energy and chemical requirements: Advanced oxidation processes like ozonation or Fenton reactions are costly and not always feasible for small to medium-scale industries. Fouling and limited lifespan of membranes: Pressure-driven filtration processes like ultrafiltration or reverse osmosis suffer from membrane fouling due to high TDS and organics.

2.3 Role of Nanotechnology in Overcoming These Challenges

Nanotechnology presents a novel and highly efficient alternative for treating textile effluents. Nanomaterials such as TiO_2 nanoparticles, graphene oxide (GO), carbon nanotubes (CNTs), and Nanozero valent iron (nZVI) possess unique physicochemical properties, including:



Fig 1. Environmental and health impacts caused by textile effluent containing dyes.

3. Nanotechnology-Based Treatment Techniques

3.1 Nano filtration Membranes

Nano filtration (NF) uses 1–10 Å pores to reject dyes and multivalent ions. Polyamide NF membranes achieve ~90% dye removal and significant COD reductions in textile wastewater Recent studies show PVDF/TiO_2 hybrid membranes reduce methylene blue by >95% in hybrid photocatalytic membrane reactors



Fig 2: How Nano filtration Works

3.2 Photocatalytic Degradation Using TiO_2 Nanoparticles

TiO_2 under UV irradiation generates •OH radicals that degrade organic pollutants. Under optimal conditions (pH 7, calcination at ~450 °C, catalyst ≈1 g/L), visible-light doped TiO_2 can remove >90% organics

A recent solar-TiO_2 hydrothermal application achieved >99% methylene blue degradation within 40 min, sustained over five cycles

3.3 Carbon-Based Nanomaterials

Graphene/GO – With SAs >2600 m²/g and abundant functional groups, GO enables high-capacity adsorption through π–π interactions, achieving >95% dye removal.

CNTs offer rapid adsorption kinetics for organics and metals but suffer from cost issues and aggregation—mitigated by surface functionalization.



Fig 3. Nanotechnology Applications in Wastewater Treatment

3.4 Nano Zero valent Iron (nZVI)

nZVI is potent for reductive degradation and heavy-metal precipitation. It degrades azo dyes in groundwater and has been deployed at ~70 pilot/full-scale sites globally

Recovery remains a challenge due to iron passivation.

3.5 Hybrid Nanocomposite Membranes

Combining nanomaterials (e.g., TiO_2, ZnO, Fe_3O_4) with polymeric membranes boosts permeability, anti-fouling, and multi-pollutant removal. Examples include PVDF/TiO_2 and GO/CNT blended membranes.

4. Nanomaterials in Water Treatment

4.1 Carbon-Based Nanomaterials

Graphene and carbon nanotubes (CNTs) offer high surface area, chemical stability, and excellent adsorption capabilities. They are effective in removing dyes, heavy metals, and pharmaceuticals

Functionalized graphene oxide (GO) and reduced graphene oxide (rGO) enhance contaminant adsorption by improving hydrophilicity and dispersibility.

4.2 Metal and Metal-Oxide Nanoparticles

Zinc oxide, titanium dioxide, and Nanozero valent iron (nZVI) are extensively studied for their antimicrobial properties and redox behaviour. These particles exhibit high reactivity and can degrade or immobilize pollutants in water

4.3 Nanocomposite Membranes

Embedding nanoparticles in polymeric membranes enhances mechanical strength, anti-fouling properties, and pollutant selectivity. These membranes can achieve multifunctionality—adsorption, separation, and catalytic degradation in a single system

Nanomaterial	Main Features	Pollutants Removed	How It Works	Efficiency
Graphene Oxide (GO)	High surface area, water-friendly	Dyes, heavy metals, medicines	Adsorbs pollutants on its surface	95–99% dye removal
Reduced Graphene Oxide (rGO)	Strong chemical bonding, good for organics	Organic pollutants, dyes	Adsorption via strong interactions	90–98%
Carbon Nanotubes (CNTs)	Tube-shaped, large surface area	Heavy metals, dyes	Traps pollutants in tubes or on surface	92–98%
Titanium Dioxide (TiO_2)	Works with UV light, safe and stable	Dyes, microbes, chemicals	Breaks down pollutants using sunlight	90–99%
Zinc Oxide (ZnO)	Works with sunlight, kills bacteria	Bacteria, phenols, dyes	Sunlight-based breakdown and disinfection	>90%, full germ removal

Nano Iron (nZVI)	Strong reducer, magnetic	Dyes, heavy metals, toxic chemicals	Transfers electrons to break down toxins	>90% metal & dye removal
GO + TiO_2 Composite	Combines strength of GO and TiO_2	Dyes, medicines	Adsorption + light-based degradation	>98%
ZnO + CNT Composite	Works faster with better light use	Dyes, metals	Better photo catalysis and reuse	~97%
Membranes with Nanoparticles	Strong, reusable, filters small particles	Dyes, germs, salts	Filters + reacts + adsorbs in one step	>95% for colour & chemicals

Table 1. Common Nanomaterials Used in Water Treatment

5. Environmental and Health Implications

While nanomaterials offer significant advantages in water treatment, their potential environmental and health impacts must be carefully considered. A major concern is the uncontrolled release of nanoparticles into aquatic ecosystems during or after the treatment process. Once in the environment, free nanoparticles can interact with living organisms, potentially causing acute ecotoxicity. Studies have shown that certain nanomaterials, such as silver nanoparticles and Nanozero valent iron (nZVI), can be toxic to aquatic species like Daphnia magna and algae, affecting reproduction, growth, and photosynthesis. Furthermore, persistent nanoparticles may undergo bioaccumulation and bio magnification, entering the food chain and posing long-term risks to animal and human health.

To mitigate these risks, several strategies are being explored. One effective approach is the use of magnetic nanocomposites (e.g., Fe_3O_4/GO or Fe_3O_4/nZVI), which can be easily separated from treated water using external magnetic fields, reducing the chance of environmental leakage. Another strategy is the immobilization of nanoparticles onto granular or polymeric supports, which enhances their stability and reusability while minimizing direct contact with biological systems. In addition, conducting life cycle assessments (LCA) and eco-toxicity evaluations is critical to understand the long-term impacts of nanomaterials, from production to disposal. These assessments help ensure that the benefits of nanotechnology in water treatment are not outweighed by unintended harm to the environment or public health.

6. Future Directions

Advancements in nanotechnology for water and textile effluent treatment are steadily moving toward sustainable, multifunctional, and scalable solutions. One of the most promising areas of ongoing research is the green synthesis of nanomaterials, which employs biological sources such as plant extracts, agricultural waste (e.g., rice husk), and marine biomass (e.g., algae) as reducing and stabilizing agents. These eco-friendly synthesis routes eliminate the need for hazardous chemicals and high-energy processes, thereby reducing environmental footprint and improving the biocompatibility of the resulting nanoparticles.

The development of magnetic hybrid nanocomposites, such as Fe_3O_4–graphene oxide–nZVI (Nanozero valent iron) systems, represents another significant direction. These materials exhibit synergistic properties—combining high reactivity and adsorption capacity with magnetic recoverability—thus enabling enhanced pollutant removal and easy post-treatment separation. Their multifunctionality allows for the simultaneous removal of dyes, heavy metals, and pathogens via adsorption, reduction, and disinfection processes, making them suitable for complex effluent matrices.

To improve the photocatalytic performance under natural sunlight, the focus has shifted to visible-light-responsive photo catalysts, particularly graphene/TiO_2 hybrids integrated with 2D layered semiconductors (e.g., g-C_3N_4, MoS_2). These advanced composites address the inherent limitations of pure TiO_2 by reducing electron–hole recombination and extending light absorption into the visible spectrum. Such materials hold potential for energy-efficient water purification systems that function effectively under ambient conditions.

Moreover, the integration of smart technologies, including real-time sensors, Internet of Things (IoT) devices, and artificial intelligence (AI)-driven optimization algorithms, is expected to revolutionize water treatment operations. These systems can dynamically monitor water quality parameters and optimize treatment conditions, enhancing overall efficiency and adaptability. Finally, increasing emphasis on pilot-scale validation and life cycle assessments (LCA) will be essential to ensure the practical scalability, cost-effectiveness, and environmental safety of nanotechnology-based treatment systems.

7. Conclusion

Nanotechnology has demonstrated substantial potential in advancing the treatment of textile and industrial wastewater. The application of various nanomaterials—including titanium dioxide (TiO_2)-based photo catalysts, carbon-based adsorbents (e.g., graphene oxide, carbon nanotubes), nanocomposite membranes, and Nanozero valent iron (nZVI)—has resulted in high pollutant removal efficiencies, often exceeding 99% for synthetic dyes and other recalcitrant organics. These nanomaterials offer multifunctional capabilities such as adsorption, catalytic degradation, disinfection, and separation, making them highly effective for complex effluent systems where conventional methods fall short.

Despite these advancements, several challenges must be addressed to facilitate large-scale implementation. Key concerns include the environmental and toxicological safety of free nanoparticles, their economic feasibility, and the sustainability of their synthesis and recovery. The unintentional release of nanoparticles into aquatic environments may pose ecological and health risks due to bioaccumulation and toxicity to non-target organisms. Therefore, eco-friendly synthesis routes, such as plant- or biomass-mediated green synthesis, are essential for minimizing environmental impact.

Additionally, there is a growing need for hybrid systems that combine multiple functions—such as magnetic separation, visible-light photo catalysis, and selective adsorption—into a single, recoverable platform. The integration of AI-based monitoring, real-time sensors, and automated controls can further optimize operational performance and energy usage in future treatment plants. Furthermore, life cycle assessments (LCA) and techno-economic analyses (TEA) should be conducted to evaluate the long-term viability, scalability, and safety of these technologies.

In conclusion, while nanotechnology has already transformed laboratory-scale water treatment strategies, its transition to real-world applications will depend on achieving a balanced integration of efficacy, environmental responsibility, and economic sustainability. Future research must continue to address these interdisciplinary challenges to enable cleaner, safer, and more efficient wastewater treatment systems.

References

1. H. S. Sultan Aljibori *et al.*, "A comprehensive review on graphene oxide based nanocomposites for wastewater treatment," *Pol. J. Chem. Technol.*, vol. 26, no. 1, pp. –, 2024.
2. B. Liu, B. Chen, and B. Zhang, "Oily wastewater treatment by nano-TiO_2-induced photocatalysis," *IEEE Nanotechnol. Mag.*, vol. 11, pp. 4–15, Jul. 2017.
3. A. O. Ibhadon and P. Fitzpatrick, "Heterogeneous photocatalysis: Recent advances and applications," *Catalysts*, vol. 3, pp. 189–218, 2013.
4. M. N. Mohammed and H. S. S. Aljibori, "Graphene oxide based nanocomposites for pollutant removal," *Res. Gate*, Jun. 2024.
5. S. Nagaraj *et al.*, "Photocatalytic advancements and applications of titanium dioxide," *ACS Sustain. Chem. Eng.*, Mar. 2025.
6. A. Karuppiah *et al.*, "Photocatalysis as an alternative for remediation of wastewater," *Materials*, vol. 8, no. 5, p. 95, 2024.
7. X. Wei, Z. Xu, and N. Wei, "Understanding water permeation in graphene oxide membranes," *arXiv*, Feb. 2014.
8. J. Park, P. Bazylewski, and G. Fanchini, "Porous graphene-based membranes for water purification," *Nanoscale*, 2017.
9. "Nanotechnology for water purification," *Wikipedia*, Feb. 2025.
10. S. Zhang *et al.*, "Adsorption of aromatic compounds by carbonaceous adsorbents," *Environ. Sci. Technol.*, 2017.
11. A. Arshad *et al.*, "Graphene/SiO_2 nanocomposites: Photocatalytic enhancement," *arXiv*, Jul. 2017.
12. G.-F. Norra *et al.*, "Chlorine-free electrochemical disinfection using graphene sponge electrodes," *arXiv*, Oct. 2021.
13. H. S. Sultan Aljibori, "Graphene oxide-based materials for water remediation," *RSC Environ. Sustain.*, 2024.
14. M. Wang, Y. Xiong, and J. Liu, "Graphene-based TiO_2 photocatalysts," *J. Mater. Chem. A*, vol. 3, no. 33, pp. 17196–17216, 2015.
15. B. Parajonnala Narasaiah *et al.*, "Bio-inspired ZrO_2 nanoparticles from Durva grass," *J. Hazard. Mater. Adv.*, 2022.
16. M. Vasiljević *et al.*, "Eco-friendly ZnO NP synthesis from citrus peel," *ACS Appl. Bio Mater.*, May 2024.
17. T.-H. Liou *et al.*, "Biowaste-derived silica–TiO_2 photocatalyst," *Arab. J. Chem.*, Jun. 2024.
18. J. Palajonnala *et al.*, "Carbon quantum dots assisted $BiFeO_3$@BiOBr catalyst," *Sci. Total Environ.*, Mar. 2024.
19. S. Yadav *et al.*, "Sugarcane bagasse green synthesis of Cu_2O NPs," *Environ. Dev. Sustain.*, Feb. 2021.
20. H. Liang *et al.*, "Fe_3O_4/rGO/Fe/MgO nanocomposites for dye degradation & H_2 evolution," *arXiv*, Nov. 2021.
21. P. Bazylewski *et al.*, "Electrochemical CNT filters for water purification," *Environ. Sci. Technol.*, 2017.
22. E. Tapire Nadres, *Toxicity and Environmental Applications of Graphene-Based Nanomaterials*, Springer, 2016.
23. V. Kodali and B. D. Thrall, *Oxidative Stress and Nanomaterial-Cellular Interactions*, Springer, 2015.
24. Z. Vasiljević *et al.*, "Rooibos tea waste ZnO composite," *J. Environ. Manage.*, Mar. 2024.
25. M. Ali *et al.*, "Green synthesis of Er-doped ZnO NPs for dye removal," *Molecules*, Jan. 2024.

26. B. Nalla *et al.*, "Transient photoconductivity in graphene oxide composites," *Nanotechnology*, 2016.
27. C. A. Denis and F. Iribarne, "Comparative study of defect reactivity in graphene," *J. Phys. Chem. C*, 2016.
28. N. Yamada *et al.*, "Nitrogen-containing graphene via XPS analysis," *Carbon*, 2016.
29. P. Park and R. Ruoff, "Chemical methods for the synthesis of graphenes," *Nat. Nanotechnol.*, vol. 4, pp. 217–224, 2009.
30. D. C. Wu *et al.*, "Graphene oxide: preparation and electrochemical applications," *Chem. Rev.*, vol. 112, pp. 6027–6053, 2012.