International Journal of Scientific Research and Engineering Development-– Volume 8 Issue 4, July Year 2025
Available at www.ijsred.com

RESEARCH ARTICLE OPEN ACCESS

Design and Optimization of Smart Grid Systems Using AI Algorithms

Hansaben Haribhai Patel*, Habibaben Vajirali Momin**
*(*Electrical Engineering, Swami Sachchidanand Polytechnic College Visnagar*
Email: hansapatel1776@gmail.com)
** (*Electrical Engineering, Swami Sachchidanand Polytechnic College Visnagar*
Email: habibamomin2@gmail.com)

Abstract:

The main research conducted is to develop smart grid systems with artificial intelligence algorithms and in a simulation approach. The proposed study plans to solve demands forecast and present energy routing and grid stability issues by including complex AI models in a dynamic energy space. LSTM networks are utilized in accurate load forecasting whereas Genetic Algorithms are used in the optimization of energy distribution and fault detection. This simulation setting proves that the suggested AI-based system brings a high level of operational efficiency, adaptability, and system fault response ability compared to the traditional methods. The experimental data proves the effectiveness of the approaches to predictive analytics and intelligent optimization in realizing the real-time, data-driven control in energy networks. This research leads to the growing domain of smart grid automation, and the model developed is scalable and resilient with good application potential to the real-world. The results justify the wider use of AI-based technologies in creating intelligent, sustainable, and forward-looking power systems.

Keywords* - *Smart Grid, Artificial Intelligence, Optimization, Machine Learning, Power Systems, Load Forecasting

I. INTRODUCTION

Smart grids are an innovative transformation of energy infrastructure that can combine digital technologies and existing energy systems enabling real-time monitoring, energy distribution, and demand response. Smart grids, unlike conventional grids, utilize bi-directional communication, enhanced sensors, and automated controls to expand the adaptability of the systems and its sustainability. Nevertheless, the increasing sophistication of energy usage patterns and the penetration of decentralized renewables has presented daunting challenges to stability, demand prediction as well as load management.



FIG 1: SMART GRID ARCHITECTURE

The need to optimize this dynamic environment has emerged as an imperative to ensure reliability, limit transmission losses, grid congestion and forced outages.

A promising strategic response to those challenges is Artificial Intelligence (AI): intelligent decision-making, predictive analytics, and adaptive control can be applied. AI enables responsiveness to grids through machine learning, evolutionary algorithms, and neural networks by helping to proactively detect faults and energy pathways. On the one hand, AI applications have progressed, and existing systems tend to use generalized models that cannot be adjusted to the context and respond in real-time. This study fills this gap by conducting a first-order study on design and optimization of smart grid systems based on AI algorithms to adaptable energy settings. This study seeks to test and develop an AI-based framework that augments operation efficiency, demand forecasting accuracy, and smart grid systems resiliency.

II. LITERATURE BACKGROUND

Innovations in smart grid in the recent past have laid much emphasis on the incorporation of artificial intelligence to handle dynamic energy requirements and make the system dynamic as well. Numerous analyses have indicated the possibility of AI in advancing power efficiency, real-time oversight, and operational direction in smart energy frameworks. A research paper suggested an energy efficient form of Wireless Body Area Networks (WBAN) incorporating smart grids and insisted on use of network optimization mechanism to enhance quality of services and minimize congestion. The integration of both adaptive scheduling as well as secured routing protocol in this framework greatly increased the throughput and network reliability depicting the feasibility of AI-based optimization techniques [1].

Researchers have introduced the design methodologies in the field of building-grid interaction to optimize energy systems to zero-energy buildings. These approaches involve repeated matching of energy generating, storing, and demand plans against grid expectations thereby creating grid-concordant operations. The reported results are significant positive changes in grid interaction measures, and lower carbon emissions at higher system cost [2].

Additionally, AI has become an innovative method in the demand response system, allowing smart load control and user interaction plans. Smart grids will be more user-centric and adaptive due to real-time consumption analysis, predictive demand scheduling, and auto-controlled devices that could be made available through machine learning techniques [3].

Nonetheless, these contributions still lack integration of AI algorithms into a adaptive, holistic optimization plan that manages the grid-wide systems as a whole. This paper intends to fill this gap with a fully developed AI-based model geared towards adapting grid optimization through focusing on real-time control, predictive analysis, and increased energy network resilience.

III. RESEARCH METHODOLOGY

The current research uses the primary research method to simulate designing and optimizing smart grid systems using artificial intelligence algorithms. This system is designed in Python and MATLAB, incorporating the machine learning, frameworks, including TensorFlow to train, test, and deploy models. The publicly available datasets of smart meters are assigned to simulated datasets relevant to the real-time grid conditions like load profiles, energy consumption patterns, and generation data [4].



FIG 2: AN ILLUSTRATION OF INTERPRETABLE ML IN THE SMART GRID.

The main AI algorithms applicable in the research are Artificial Neural Networks (ANN) and forecasting of demands, Genetic Algorithms (GA) and system optimization, and Long Short-term Memory (LSTM) and networks of load forecasting. The temporal dependences, nonlinearity, and flexibility to the complexity of the grid performances attribute to the selection of these models by reason. The leading areas to optimize would include load balancing, fault tracing, energy routing, to maintain grid stability and efficiency [5].

There are several variables such as the Mean Squared Error (MSE) to quantify the accuracy of the prediction, the energy efficiency ratios, and a stability index to measure how well a system can be maintained in a state of perfect predictability with changing loads. The approach provides strong testing of AI models within a simulated system, which provides useful information about their scalability, performance, and potential use in future smart grids.

IV. EXPERIMENTAL SETUP AND RESULTS

The study environment was simulated using Python and MATLAB with the TensorFlow and Simulink modules and appended to emulate real-time conditions of operations in a smart grid. The system is defined by the data-set insertion module, AI-plan prediction module, optimisation module and performance evaluation module. Examples of input data were power consumption profiles, renewable generation variability and system load variations with synthetically generative smart meter data that simulate real world design [6].

ANN and long short-term memory models able to predict loads, optimise swarm control and energy paths to load, using genetic Algorithms (GA) and Particle Swarm Optimization (PSO). The training and validation of models relied on the training data-testing data split with the cross-validation to ensure generalizability. ANN compared similarly with short time load variation predictions but LSTM was more precise in long time moral bounds because it had an ability to capture time ties. The GA showed its definition of sound convergence features and low computational cost as a real time decision tool during the optimization step. PSO proved to be effective, but not as effective in dynamic grid characterizes [7]. Compared with PSO, the GA had better performance when it was used with predictive models in fault mitigation and energy routing.

According to the results, LSTM-GA model was better at demand forecasting and performance optimization, together. LSTM compared to ANN-based configurations responded smoother to load spikes, leading to a more stable grid. The simulation has shown significant efficiency in power distillation and minimal transmission losses. Additionally, the fault detecting algorithms with AI allowed this system to respond quicker to anomalies, making the grid infrastructure resilient. Generally, the experimental results confirm the realization potential of the proposed framework to facilitate adaptive control approaches, effective load management, and enhanced reliability in smart grid operations under different working conditions.

V. DISCUSSION

These research findings highlight the usefulness of models with AI in meeting some of the primary smart grid goals (x demand forecasting, energy efficiency, and operational reliability). Hybridization between LSTM and GA includes major gains compared to the old rule-based or statistical models, especially dealing with time and non-linear variables. This adaptive feature allows better forecasting and optimal energy routing, which helps to lessen loss and improve grid stability directly [8].

The proposed framework has a higher potential on real-time decision-making and adaptive recovery with load variation than conventional systems. The modular internal design and the use of popular platforms grant it great potential in viable deployments in urban and distributed energy systems. The method is, however, at present hampered by computational resource needs, and high-quality input data are necessary. Potential future enhancements can include the decrease in processing latency and the use of edge computing to decentralize execution and hence, improving scalability and responsiveness in real-world deployment [9].

VI. CONCLUSION AND FUTURE SCOPE

This study provides the main research of AI algorithms in the design and optimization of smart grid systems. A combination between LSTM and GA yielded correlating better demand predictions accuracy, energy routing efficiency, and system stability than conventional methods. The suggested framework helps improve smart, dynamic grid infrastructure that will have the ability to react to real-time operating issues.

Future directions are to consider the scalability of the model to large-scale grid settings, real-time implementation using edge computing, and the integration of cybersecurity solutions, to protect the integrity of data and the management control of more interconnected energy systems.

VII. REFERENCES

[1] M. M. Kamruzzaman and O. Alruwaili, “Energy efficient sustainable Wireless Body Area Network design using network optimization with Smart Grid and Renewable Energy Systems,” *Energy Reports*, vol. 8, pp. 3780–3788, Nov. 2022, doi: https://doi.org/10.1016/j.egyr.2022.03.006.

[2] S. Jia, K. Sheng, D. Huang, K. Hu, Y. Xu, and C. Yan, “Design optimization of energy systems for zero energy buildings based on grid-friendly interaction with smart grid,” *Energy*, vol. 284, pp. 129298–129298, Dec. 2023, doi: https://doi.org/10.1016/j.energy.2023.129298.

[3] M. A. Khan, A. M. Saleh, M. Waseem, and I. A. Sajjad, “Artificial Intelligence Enabled Demand Response: Prospects and Challenges in Smart Grid Environment,” *IEEE Access*, vol. 11, pp. 1477–1505, 2023, doi: https://doi.org/10.1109/access.2022.3231444.

[4] Sathish Kaveripakam and Ravikumar Chinthaginjala, “Optimal path selection and secured data transmission in underwater acoustic sensor networks: LSTM-based energy prediction,” *PloS one*, vol. 18, no. 9, pp. e0289306–e0289306, Sep. 2023, doi: https://doi.org/10.1371/journal.pone.0289306.

[5] A. Mehdary, A. Chehri, A. Jakimi, and R. Saadane, “Hyperparameter Optimization with Genetic Algorithms and XGBoost: A Step Forward in Smart Grid Fraud Detection,” *Sensors*, vol. 24, no. 4, p. 1230, Jan. 2024, doi: https://doi.org/10.3390/s24041230.

[6] Md. M. A. Moni, M. Niloy, A. H. Chowdhury, F. J. Khan, Md. F.-U.-A. Juboraj, and A. Chakrabarty, “Comparative Analysis of Process Scheduling Algorithm using AI models,” *IEEE Xplore*, Dec. 01, 2022. https://ieeexplore.ieee.org/document/10055395 (accessed Mar. 09, 2024).

[7] A. M. Shaheen, E. E. Elattar, R. A. El-Sehiemy, and A. M. Elsayed, “An Improved Sunflower Optimization Algorithm-Based Monte Carlo Simulation for Efficiency Improvement of Radial Distribution Systems Considering Wind Power Uncertainty,” *IEEE Access*, vol. 9, pp. 2332–2344, 2021, doi: https://doi.org/10.1109/access.2020.3047671.

[8] F. R. Albogamy *et al.*, “Real-Time Scheduling for Optimal Energy Optimization in Smart Grid Integrated With Renewable Energy Sources,” *IEEE Access*, vol. 10, pp. 35498–35520, 2022, doi: https://doi.org/10.1109/access.2022.3161845.

[9] M. Khalid, “Smart grids and renewable energy systems: Perspectives and grid integration challenges,” *Energy Strategy Reviews*, vol. 51, pp. 101299–101299, Jan. 2024, doi: https://doi.org/10.1016/j.esr.2024.101299.

