International Journal of Scientific Research and Engineering Development-– Volume 9 Issue 2, Mar-Apr 2026
Available at www.ijsred.com

RESEARCH ARTICLE OPEN ACCESS

Advancing Glaucoma Detection Using Deep Learning Techniques – A Survey

Priya Tiwari[1], Seema Kirar[2]
[1]Research Scholar, [2]Assistant Professor
[1,2]Bansal Institute of Science and Technology, Bhopal

Abstract

Glaucoma remains one of the most significant causes of irreversible blindness worldwide, primarily due to its progressive nature and the lack of noticeable symptoms during early disease stages. The increasing availability of digital retinal imaging data and advancements in artificial intelligence have facilitated the development of automated diagnostic systems capable of supporting ophthalmologists in clinical decision-making. This review paper synthesizes methodological insights and empirical findings derived from a deep learning-based dissertation framework focused on multi-class glaucoma detection using retinal fundus images. The reviewed framework employs a convolutional neural network architecture designed to automatically extract discriminative visual features and classify retinal images into ten diagnostic categories. Emphasis is placed on balanced performance evaluation using accuracy, precision, recall, F1-score, confusion matrix analysis, and training–validation convergence behavior. The reported experimental findings demonstrate an overall classification accuracy of 78.73%, with macro precision, recall, and F1-score values of 0.7889, 0.7873, and 0.7866, respectively. The review critically discusses methodological strengths, class-wise performance variations, interpretability considerations, and real-world deployment challenges. The analysis concludes that deep learning-driven glaucoma screening systems represent a promising decision-support paradigm when designed with methodological rigor, ethical responsibility, and clinical integration in mind.

Keywords: Glaucoma Detection, Deep Learning, CNN, Retinal Fundus Imaging, Multi-Class Classification, Ophthalmic AI

1. Introduction

Glaucoma represents one of the most significant causes of irreversible blindness worldwide, and its global burden is expected to rise steadily with increasing life expectancy and population aging. The progressive nature of the disease, combined with its asymptomatic presentation during early stages, makes timely detection particularly challenging. In many cases, patients remain unaware of vision deterioration until substantial optic nerve damage has already occurred. Consequently, early diagnosis and appropriate clinical intervention are essential for preserving visual function and preventing permanent disability. Conventional glaucoma diagnostic practices typically involve a combination of intraocular pressure measurement, visual field analysis, optic nerve head evaluation, and interpretation of retinal imaging data. While these procedures are clinically validated and widely adopted, they are often time-consuming, dependent on specialist expertise, and constrained by the availability of advanced diagnostic equipment. Such limitations pose significant challenges for large-scale screening programs, particularly in low-resource or rural healthcare environments where access to trained ophthalmologists is limited.

In recent years, the rapid digitization of ophthalmic imaging systems and the widespread adoption of electronic medical data management have resulted in the generation of vast volumes of retinal fundus images. This data-rich environment has created new opportunities for the application of artificial intelligence techniques aimed at improving diagnostic efficiency and scalability. Deep learning, especially convolutional neural networks, has emerged as a transformative paradigm in medical image analysis due to its ability to automatically learn hierarchical feature representations directly from raw visual data. Unlike traditional image processing approaches that rely on handcrafted feature engineering, CNN-based models can capture subtle structural

 ©IJSRED: All Rights are Reserved

variations in retinal anatomy, including changes in the optic disc, optic cup, and surrounding retinal nerve fiber layers. Such capabilities are particularly valuable for glaucoma detection, where pathological indicators may be visually subtle and distributed across multiple image regions. Within this evolving research landscape, the reviewed dissertation proposes a deep learning-based framework designed to perform multi-class glaucoma classification using retinal fundus images. By moving beyond conventional binary diagnostic formulations, the proposed approach acknowledges glaucoma as a progressive condition characterized by varying severity levels. This multi-class perspective enhances clinical relevance by enabling more nuanced categorization of disease stages, thereby supporting informed treatment planning and risk stratification.

The framework also emphasizes balanced performance evaluation, training stability, and methodological transparency to ensure reliable diagnostic support. This review paper synthesizes the conceptual foundations, methodological contributions, and empirical findings of the proposed system while situating it within broader advancements in intelligent ophthalmic screening technologies. Through critical analysis and integration of existing research insights, the review aims to highlight both the potential and the challenges of deep learning-driven glaucoma detection in modern healthcare systems.



Figure 1: Conceptual overview of deep learning–based automated glaucoma detection using retinal fundus image analysis.

2. Evolution of Automated Glaucoma Detection and Deep Learning Integration

The evolution of automated glaucoma detection reflects broader developments in medical image analysis, progressing from traditional rule-based computational techniques to sophisticated deep learning-driven diagnostic frameworks. Early research efforts primarily focused on handcrafted feature extraction methods designed to quantify clinically significant structural indicators associated with glaucomatous damage. These features included parameters such as the cup-to-disc ratio, neuroretinal rim thickness, optic disc boundary characteristics, and vascular density patterns. By translating ophthalmological knowledge into computational descriptors, researchers aimed to create objective and reproducible diagnostic tools capable of assisting clinicians in identifying disease-related abnormalities.

Although these approaches demonstrated moderate classification accuracy in controlled experimental datasets, their performance was often constrained by sensitivity to imaging conditions, anatomical variability, and noise. Variations in illumination, camera resolution, and patient-specific retinal morphology frequently reduced the robustness and generalizability of handcrafted feature-based systems when applied in real-world clinical environments. The introduction of machine learning algorithms marked a significant paradigm shift toward data-driven glaucoma detection frameworks. Supervised learning techniques such as support vector machines, k-nearest neighbors, and decision trees enabled automated classification of retinal images based on labeled training data. These models improved diagnostic consistency and scalability compared to purely rule-based approaches by learning statistical relationships between extracted features and disease categories. However, despite these advantages, machine learning models remained heavily dependent on the quality and relevance of manually engineered features. Feature selection and representation required substantial domain expertise, and models often struggled to capture complex, non-linear visual patterns associated with early glaucomatous changes. Consequently, the limitations of feature engineering motivated the exploration of more adaptive analytical methodologies.

 ©IJSRED: All Rights are Reserved

The emergence of deep learning, particularly convolutional neural networks, fundamentally transformed the landscape of medical image analysis and automated glaucoma detection. CNN architectures introduced an end-to-end learning paradigm in which feature extraction and classification are jointly optimized during training. Through layered convolutional operations, these models learn hierarchical representations ranging from low-level edge detection to high-level structural pattern recognition. This capability enables deep learning systems to identify subtle retinal variations that may not be readily apparent through handcrafted descriptors or traditional machine learning pipelines. As a result, deep learning-based glaucoma detection frameworks have demonstrated improved diagnostic performance, scalability, and adaptability across diverse datasets. Recent research trends increasingly emphasize the development of multi-class glaucoma classification systems that capture the progressive nature of disease severity rather than simplifying diagnosis into binary categories. Such approaches align more closely with clinical decision-making processes, which require detailed staging information for treatment planning and risk assessment. The reviewed dissertation reflects this evolving perspective by proposing a convolutional neural network architecture optimized for ten-class retinal image classification.

By enhancing diagnostic granularity and emphasizing balanced performance evaluation, this framework contributes to the ongoing integration of deep learning technologies into intelligent and clinically relevant ophthalmic screening solutions.

Table 1: Representative Research Themes in Deep Learning-Based Glaucoma Detection

Research Focus	**Methodological Approach**	**Key Contribution**
Early automated detection	Handcrafted features	Structural parameter quantification
Machine learning classification	SVM / Decision Trees	Improved consistency
Deep learning frameworks	CNN architectures	End-to-end feature learning
Multi-class diagnosis	Advanced CNN models	Clinically meaningful staging

3. CNN-Based Methodological Framework for Glaucoma Classification

The reviewed dissertation presents a systematically designed methodological framework for automated glaucoma detection that integrates data preparation, preprocessing, deep learning model development, training optimization, and comprehensive performance evaluation into a cohesive experimental pipeline. Such structured methodological design is essential in medical image analysis research, where diagnostic reliability, reproducibility, and clinical relevance must be carefully ensured. The framework is centered on retinal fundus image analysis due to the modality's non-invasive nature and its ability to capture detailed structural information related to optic nerve health and glaucomatous progression.

A key strength of the proposed approach lies in the use of a balanced dataset comprising retinal fundus images distributed equally across ten diagnostic classes. Balanced class representation plays a crucial role in multi-class classification tasks by reducing model bias toward majority categories and enabling fair performance comparison across disease stages. Stratified data partitioning strategies were employed to divide the dataset into training and testing subsets while preserving class distribution. This approach ensures that the model is exposed to diverse retinal patterns during learning while maintaining unbiased evaluation conditions for assessing generalization capability on unseen samples.

To enhance image quality and facilitate stable learning behaviour, a comprehensive preprocessing pipeline was implemented prior to model training. All images were resized to a fixed spatial resolution to ensure uniform input dimensionality compatible with convolutional neural network processing requirements. Pixel intensity normalization was applied to standardize illumination conditions and improve numerical stability during optimization. Additional preprocessing operations such as noise reduction and contrast enhancement were performed to improve visibility of clinically relevant retinal structures, including the optic disc and vascular patterns. Furthermore, data augmentation

 ©IJSRED: All Rights are Reserved

techniques including rotation, horizontal and vertical flipping, and minor scaling transformations were incorporated dynamically during training. These augmentation strategies effectively increased dataset diversity, enabling the model to learn invariant features and improving robustness to real-world imaging variability.

The core diagnostic component of the framework is a convolutional neural network architecture designed to balance feature extraction capability with computational efficiency. Multiple convolutional layers were utilized to capture hierarchical retinal patterns, with early layers focusing on low-level textures and edges, and deeper layers learning disease-specific structural representations. Max-pooling operations were interleaved to reduce spatial dimensionality and improve translational invariance. Dropout regularization was incorporated to mitigate overfitting by randomly deactivating neurons during training, thereby promoting generalized feature learning. Following convolutional processing, dense fully connected layers integrated extracted features for classification. The final softmax output layer, consisting of ten neurons, generated probabilistic predictions corresponding to the defined diagnostic categories. Model optimization was performed using the Adam optimizer and categorical cross-entropy loss function, with a batch size of 32 and early stopping mechanisms based on validation performance trends to ensure stable convergence and controlled training duration.

4. Performance Evaluation and Learning Behaviour Analysis

The performance evaluation of the proposed deep learning–based glaucoma detection framework provides important insight into the diagnostic capability, reliability, and generalization behaviour of the developed convolutional neural network model. Given the medical significance of glaucoma screening, model assessment was conducted using multiple quantitative metrics to ensure a comprehensive understanding of classification performance across all diagnostic categories.

The experimental findings demonstrate that the model achieved an overall classification accuracy of 78.73%, which represents a meaningful and practically relevant outcome for a ten-class retinal image classification problem. Multi-class medical imaging tasks are inherently complex due to subtle inter-class variations and overlapping pathological characteristics; therefore, achieving this level of accuracy indicates that the model successfully learns discriminative visual representations associated with glaucomatous progression. Beyond overall accuracy, macro-averaged precision, recall, and F1-score values of 0.7889, 0.7873, and 0.7866, respectively, provide further evidence of balanced classification performance. These closely aligned metrics suggest that the model maintains consistent predictive behaviour across diagnostic categories rather than disproportionately favoring specific classes. From a clinical standpoint, such balance is particularly important, as both false positives and false negatives can have significant implications. High recall ensures that a substantial proportion of glaucomatous cases are correctly identified, thereby reducing the risk of missed diagnoses that could result in irreversible vision loss. Similarly, adequate precision contributes to minimizing unnecessary referrals or additional clinical investigations. A more granular class-wise analysis reveals variations in predictive reliability that align with clinical expectations. Visually distinctive categories demonstrate strong performance, with Class 1 achieving an F1-score of 0.8811 and Class 8 recording an F1-score of 0.8825.

These results indicate that the structural retinal features associated with these classes are sufficiently distinguishable within the learned feature space. In contrast, comparatively lower recall values observed for Classes 2 and 3 highlight the inherent diagnostic challenges associated with borderline or early-stage glaucoma. Such stages often exhibit subtle morphological changes that overlap with normal anatomical variability, making precise classification difficult even for experienced ophthalmologists. Confusion matrix analysis reinforces this interpretation by showing that misclassifications primarily occur between adjacent disease categories, reflecting realistic clinical ambiguity rather than systematic model failure. The analysis of training and validation learning curves further confirms the robustness of the proposed framework. Training accuracy increased progressively from approximately 37% in initial epochs to around 83%, while validation

 ©IJSRED: All Rights are Reserved

accuracy stabilized near 80%, indicating effective generalization to unseen data. Concurrently, training loss decreased significantly from about 1.7 to 0.6, with validation loss converging at a similar level. The absence of significant divergence between training and validation trends suggests controlled overfitting and stable convergence behaviour.

Collectively, these performance insights validate the suitability of the adopted CNN architecture and training strategy for automated glaucoma classification in clinically relevant screening scenarios.

5. Interpretability, Ethical Considerations, and Clinical Integration

As artificial intelligence-driven diagnostic systems continue to gain prominence in ophthalmology, considerations related to interpretability, ethical responsibility, and seamless clinical integration have become increasingly significant. Automated glaucoma detection frameworks based on deep learning offer substantial advantages in terms of scalability, consistency, and processing efficiency; however, their successful adoption in real-world healthcare settings depends not only on predictive performance but also on transparency, trustworthiness, and alignment with clinical practice. Convolutional neural networks, despite demonstrating strong capability in extracting complex visual patterns from retinal fundus images, are often criticized for functioning as "black-box" models. These systems generate classification outputs without explicitly revealing the reasoning process underlying their predictions. In clinical environments where diagnostic decisions carry serious consequences, such opacity can reduce confidence among ophthalmologists and limit the practical utility of automated screening tools.

The reviewed research acknowledges these challenges and emphasizes the role of comprehensive performance evaluation strategies as indirect mechanisms for enhancing interpretability. By employing balanced metrics such as precision, recall, and F1-score alongside confusion matrix analysis, the framework provides insight into class-wise prediction behaviour and potential sources of error. Visualization of training and validation performance trends further contributes to understanding model stability and generalization capability. These analytical tools enable clinicians and researchers to assess whether the model exhibits systematic bias or unpredictable behaviour, thereby supporting informed decision-making regarding its deployment. Although such approaches do not fully resolve the inherent opacity of deep learning systems, they represent important steps toward building trust through methodological transparency and rigorous evaluation. Ethical considerations also play a central role in the development and implementation of automated glaucoma detection systems. The use of retinal imaging data involves handling sensitive medical information, necessitating strict adherence to data protection principles.

The reviewed framework incorporates anonymization procedures to ensure that personally identifiable patient details are excluded from the dataset, thereby safeguarding privacy and confidentiality. Additionally, the deliberate use of a balanced dataset helps mitigate algorithmic bias that could otherwise lead to unequal diagnostic performance across disease categories. Responsible deployment further requires careful validation across diverse populations and imaging conditions to prevent unintended disparities in healthcare outcomes. From a clinical integration perspective, the proposed system is explicitly positioned as a decision-support tool designed to assist rather than replace ophthalmologists. Human oversight remains essential, particularly in borderline cases where automated predictions may reflect diagnostic uncertainty. By combining computational efficiency with expert clinical judgment, such hybrid approaches can enhance screening workflows, reduce diagnostic workload, and improve consistency in glaucoma detection. Ultimately, the successful translation of deep learning-based diagnostic frameworks into routine ophthalmic practice depends on maintaining a balanced focus on technical performance, ethical responsibility, interpretability, and clinician-centered system design.

6. Research Gaps and Future Directions

Despite the encouraging performance demonstrated by recent deep learning–based glaucoma detection frameworks, several research gaps continue to limit their full clinical applicability and scalability. One of the most significant challenges lies in the reliable detection of early-stage glaucoma. In the initial phases of the

 ©IJSRED: All Rights are Reserved

disease, structural alterations in the optic nerve head and retinal nerve fiber layer are often minimal and may overlap considerably with normal anatomical variation. This subtlety makes accurate classification difficult not only for automated systems but also for experienced ophthalmologists. As a result, current convolutional neural network models frequently exhibit reduced recall for borderline or early disease categories, highlighting the need for more sensitive feature learning mechanisms capable of capturing fine-grained retinal changes without increasing false positive rates. Another important limitation concerns the generalization capability of deep learning models across diverse datasets and clinical environments. Many glaucoma detection systems are trained and evaluated using datasets collected under specific imaging conditions, demographic distributions, or device characteristics. When deployed in real-world settings involving different camera technologies, illumination conditions, or population characteristics, model performance may degrade due to domain shift. Addressing this challenge requires the development of robust cross-dataset validation strategies, domain adaptation techniques, and larger multi-center retinal imaging datasets that better reflect real-world variability. Ensuring equitable diagnostic performance across populations is also essential for preventing algorithmic bias and maintaining trust in automated screening systems. Future research directions increasingly emphasize the integration of multimodal diagnostic information to enhance predictive reliability. Combining retinal fundus images with complementary clinical data such as optical coherence tomography measurements, intraocular pressure readings, and visual field assessments may enable more comprehensive modeling of glaucomatous progression. Additionally, the incorporation of explainable artificial intelligence techniques is gaining attention as a means of improving interpretability and clinician acceptance. Visualization tools that highlight regions of interest within retinal images can provide valuable insight into model reasoning and support more transparent decision-making processes. The development of lightweight and computationally efficient neural network architectures also represents a critical area for advancement, particularly in the context of large-scale screening initiatives and deployment in resource-constrained environments. While deep and complex models may achieve marginal performance improvements, their high computational requirements can hinder practical implementation. Optimized architectures that balance accuracy with efficiency are therefore essential for enabling integration into portable fundus imaging devices and tele-ophthalmology platforms. Ultimately, bridging the gap between experimental research prototypes and real-world clinical deployment will require rigorous external validation, seamless workflow integration, adherence to regulatory standards, and sustained collaboration between engineers, clinicians, and policymakers to ensure safe, effective, and scalable glaucoma detection solutions.

7. Conclusion

This review paper has synthesized methodological concepts, experimental findings, and clinical implications derived from a deep learning–based framework for automated glaucoma detection using retinal fundus images. The reviewed research demonstrates that convolutional neural network architectures can effectively learn discriminative visual representations associated with glaucomatous progression and perform multi-class classification across ten diagnostic categories with meaningful accuracy. The reported overall classification accuracy of 78.73%, along with closely aligned macro-averaged precision, recall, and F1-score values, reflects balanced predictive performance and highlights the capability of the proposed framework to manage the inherent complexity of multi-class medical image analysis tasks.

In addition to aggregate metrics, class-wise evaluation and confusion matrix analysis reveal clinically plausible misclassification patterns, particularly between adjacent disease stages where structural retinal differences are subtle. Such findings reinforce the realism of the model's behavior and suggest that the observed errors are more closely related to diagnostic ambiguity than methodological limitations. The analysis of learning behaviour further strengthens the credibility of the proposed approach. Training and validation performance trends demonstrate stable convergence, controlled overfitting, and effective generalization to unseen retinal images. These characteristics are essential for medical screening applications, where model reliability and

 ©IJSRED: All Rights are Reserved

consistency directly influence diagnostic decision-making processes. By integrating structured preprocessing strategies, balanced dataset design, and regularization mechanisms within the training pipeline, the reviewed framework establishes a robust methodological foundation for intelligent glaucoma detection systems. Moreover, the emphasis on multi-class classification enhances clinical relevance by enabling more nuanced categorization of disease severity, thereby supporting treatment planning, risk stratification, and patient monitoring.

Despite these promising outcomes, several challenges remain that warrant further investigation. Issues related to model interpretability, cross-dataset generalization, and real-world deployment feasibility continue to shape the future research agenda in deep learning–based ophthalmic diagnosis. The integration of explainable artificial intelligence techniques, multimodal diagnostic data, and lightweight computational architectures represents potential avenues for improving both performance and clinical acceptance. Importantly, the reviewed research positions automated glaucoma detection systems as decision-support tools rather than autonomous diagnostic replacements, underscoring the necessity of human oversight and ethical responsibility in healthcare innovation. In conclusion, deep learning-driven glaucoma screening frameworks offer substantial potential to enhance accessibility, improve diagnostic consistency, and facilitate early intervention strategies aimed at preventing avoidable vision loss. When developed within clinically aligned, ethically grounded, and methodologically rigorous frameworks, such intelligent diagnostic technologies can contribute significantly to the transformation of modern ophthalmic care and population-level eye health management.

References

1. X. C. Ling et al., “Deep Learning in Glaucoma Detection and Progression Using Fundus Photography and OCT,” *Biomedicines*, 2025. (MDPI)
2. M. Ashtari-Majlan et al., “Glaucoma Diagnosis in the Era of Deep Learning: A Survey,” *Expert Systems with Applications*, 2024. (ScienceDirect)
3. C. N. Yadahalli et al., “Detection of Glaucoma Using Deep Learning Algorithms,” *Procedia Computer Science*, 2025. (ScienceDirect)
4. V. Guntreddi et al., “Deep Learning-Based Ensemble Framework for Glaucoma Detection,” *Results in Engineering*, 2025. (ScienceDirect)
5. M. Kalra et al., “Advancements in Deep Learning for Glaucoma Detection from Retinal Images,” *Journal of Ophthalmic AI Research*, 2025. (Springer Link)
6. S. Islam et al., “Novel Deep Learning Model for Glaucoma Detection Using Fusion of Fundus and OCT Images,” *Sensors*, 2025. (MDPI)
7. J. Prakash et al., “DB-SegNet: Optimized Deep Learning Framework for Early Glaucoma Detection,” *Scientific Reports*, 2025. (Nature)
8. D. Meedeniya et al., “Deep Learning Approaches for Glaucoma Identification Using Retinal Fundus Images: A Systematic Review,” *Informatics in Medicine*, 2025. (ScienceDirect)
9. W. H. Abdulsalam et al., “Automated Glaucoma Detection Techniques: A Literature Review,” *Engineering, Technology & Applied Science Research*, 2025. (etasr.com)
10. E. E. Hwang et al., “Utilization of Image-Based Deep Learning in Multimodal Glaucoma Detection,” *Ophthalmology Science*, 2025. (ophthalmologyscience.org)
11. J. N. K. et al., “Early Detection of Glaucoma Using CNN Feature Visualization,” *Computer Methods in Biomechanics and Biomedical Engineering: Imaging & Visualization*, 2024. (Taylor & Francis Online)
12. Y. Y. Chiang et al., “Deep Learning Evaluation of Glaucoma Detection in High Myopia Using Fundus Photographs,” *Biomedicines*, 2024. (MDPI)
13. A. Aljohani et al., “Hybrid Federated Deep Learning Framework for Glaucoma Detection,” *BMC Medical Informatics and Decision Making*, 2024. (Springer Link)
14. “Glaucoma Detection Using Explainable AI and Deep Learning,” *EAI Endorsed Transactions on Pervasive Health and Technology*, 2024. (publications.eai.eu)

 ©IJSRED: All Rights are Reserved

15. "Glaucoma Detection Using Image Processing and Deep Learning Techniques," *International Journal of Intelligent Systems and Applications in Engineering*, 2024. (IJISAE)
16. J. Du et al., "HM-VGG: Hybrid Multimodal Deep Learning Model for Early Glaucoma Diagnosis," arXiv, 2024. (arXiv)
17. Y. Nawar et al., "DiffuPT: Class Imbalance Mitigation for Glaucoma Detection Using Diffusion Models," arXiv, 2024. (arXiv)
18. M. Ashtari-Majlan et al., "Spatial-Aware Transformer-GRU Framework for 3D OCT-Based Glaucoma Diagnosis," arXiv, 2024. (arXiv)
19. L. Pascal et al., "Multi-Task Deep Learning Model for Glaucoma Detection from Fundus Images," *Scientific Reports*, 2023. (Nature)
20. R. Hussain and H. Basak, "UT-Net: Transformer-Based Joint Segmentation Framework for Glaucoma Detection," arXiv, 2023. (arXiv)
21. S. Kinder et al., "Optic Cup and Disc Segmentation Using Artificial Intelligence for Glaucoma Screening," *Translational Vision Science & Technology*, 2025. (reviewofophthalmology.com)
22. H. Chen et al., "Multimodal Deep Learning Neural Network for Glaucoma Detection in Primary Care Cohorts," *Ophthalmology Science*, 2025. (reviewofophthalmology.com)
23. S. Islam et al., "Multimodal Fusion CNN Framework for Automated Glaucoma Detection," *PMC Open Access Study*, 2025. (PMC)
24. "Deep Learning and Multimodal Integration in Glaucoma Detection: State-of-the-Art Review," *ICSCSA Conference*, 2025. (ResearchGate)
25. "Glaucoma Detection Using Deep Learning and Prompt Engineering Techniques," *medRxiv Preprint*, 2025. (medrxiv.org)

 ©IJSRED: All Rights are Reserved