

Concrete Ribbed Slabs: Review of Structural Performance, Design Methodologies, and Recent Research Developments

Baraa Talib Omran, Prof. Dr Hossam Ali Mohamed

Construction and Building Engineering Techniques Department, Middle Technical University, Al-Musayyib Technical College

Abstract

In this review, a novel ribbed ground slab (RGS) system without mid-span support for underground buildings is proposed, and the mechanics model of the RGS is established. Because they lower both the amount of concrete and the total weight of the structure, the latter being the most significant, ribbed slabs are very common in reinforcement concrete building. The review addresses the basic one-way ribbed slab structural system with its major parts, i.e. concrete topping, longitudinal ribs, reinforcement and supports. Special emphasis is placed on flexural performance, shear capacity, deflection, cracking and serviceability criteria. In addition, conventional design methodologies that utilize traditional reinforced concrete design principles and numerical methods particularly finite element (FE) analysis to predict the structural behaviour under various loading conditions are presented. Comparative studies demonstrate the effects of rib spacing, rib depth, screed thickness, reinforcement configuration, and material properties on structural efficiency and performance. Recent trends such as the use of fiber reinforced concrete, light weight materials, sophisticated numerical modeling, vibration control, fire resistance and sustainable design are also discussed. A numerical example is presented to illustrate the calculation of equivalent line load, maximum bending moment and support shear for simply supported ribbed slab. Major gaps for future research are long-term behavior, experimental verification of numerical modeling, construction variation, and linking structural performance with that of environment. Results show that to have a good design of ribbed slab, strength, stiffness, serviceability, material efficiency and constructability should be considered properly.

Keywords: Concrete ribbed slabs; structural performance; flexural behavior; shear resistance; finite element analysis; serviceability; reinforced concrete design; sustainability.

1. Introduction

Concrete ribbed slabs are fairly common in reinforced concrete construction due to the fact that they offer a good structural solution with reduced self-weight and sufficient load-carrying capacity and stiffness. In comparison to traditional solid slabs, ribbed slabs are made up of a relatively thin concrete cover supported on a number of reinforced concrete ribs.[1]

These ribs are the main load resisting elements and the topping carries out load spreading and also is a contributing member to the flexural strength of the section. The high structural

performance of ribbed slabs is due to the optimal concrete allocation in the cross-section. Concrete Is Maintained in Areas Where It Is Most Effective in Resisting Compression while Voids Between Ribs Minimize Material Usage. Such an arrangement is able to reduce the dead load on the beams, columns and foundations by that much, which may lead to a better economy for the whole structure .Nevertheless, the behavior of ribbed slabs is affected by a number of interacting parameters such as concrete compressive strength, reinforcement ratio, rib spacing, rib width and depth, thickness of topping, loading conditions and support arrangement. Ultimate strength considerations are not at the only structural design criteria – service conditions have to be met, also with regard to cracking, deflection, vibration, durability and fire resistance.[2]

These aspects are being studied more often with the use of the finite element method, experimental investigation, alternative concrete types, as well as some optimization approaches in recent studies.[3]

Hence, the structural behavior, analytical design methods, numerical modeling techniques, and new trends in research on concrete ribbed slabs are presented in this review. It also points out research gaps that could lead to the design of more efficient, safer ,and greener floor systems. The form of the structure should be determined by the span, the load, the building function, the construction technology, and the relevant codes of practice.[4]




Figure 1. Conceptual cross-section illustrating the concrete topping, ribs, reinforcement, and voids. The dimensions and reinforcement shown are schematic and are not intended for construction.

The concrete slab ties together the ribs and transfers loads among them, as seen in Figure 1. The ribs give the structural depth required to resist bending and shear, and the voids lessen the amount of concrete inside the floor system. The specific reinforcement configuration and support conditions should be determined by structural design.[5]

2. Structural Configuration and Classification of Ribbed Slabs

Generally concrete ribbed slabs may be divided into the so-called one-way and two-way systems based on the ribs layout and load transfer directions. Two-way ribbed slabs can be considered as a grid of beams with ribs extending in two perpendicular directions. One-way ribbed slabs have parallel ribs and mainly transfer loads in one direction. [6]

They are generally employed in situations where structural configuration results in fairly rectangular floor panels with well-defined supports edges. A two-way ribbed slab consists of ribs running in two orthogonal directions, which makes it possible to span a load over a two-dimensional matrix. Such systems may be applicable for floor panels with roughly equal spans in two directions, at least, under certain conditions of support and structural design. The basic elements in a ribbed slab are concrete topping, ribs, reinforcement and inter ribs. [7]

The topping spreads loads and sometimes functions as the compression flange of a T-shaped beam. The ribs give the necessary depth for flexural strength and house the major longitudinal reinforcement. It might be necessary to provide transverse reinforcement to counteract shear and to confine the core, based on the design. The type of structure to be used must be determined by the span length, imposed loads, architectural requirements, methods of construction, and standards of design. [8]




Figure 2. Typical configuration of a one-way concrete ribbed slab
Cross-sectional schematic (not to scale)

Figure 2. Schematic cross section with concrete topping, ribs, reinforcement and voids The dimensions and reinforcement are schematic and not for construction. As shown in Figure 2, the concrete topping which joins the ribs and spans over them evenly distributes the loads. The ribs give the structural depth required to withstand bending and shear and the voids reduce the amount of concrete in the floor system. The real pattern of reinforcement and the support details must be determined by structural design.[9]

3. Structural Performance of Concrete Ribbed Slabs

3.1 Flexural behavior

The flexural behavior is the main index to assess the performance of ribbed slab. When a slab is loaded vertically, bending moments are induced in the ribs, which cause compression in one portion of the cross-section and tension in the other. Since concrete's tensile strength is comparatively low, tensile stresses are counteracted by longitudinal reinforcement in the tensile zone after it cracks. For a simply supported rib with a uniformly distributed load, the maximum bending moment is given by the classical beam formula[10]:

$$M_{max} = \frac{wL^2}{8} \quad (1)$$

where M_{max} is the maximum bending moment, w is the uniformly distributed line load acting on the rib, and L is the span length.

It can be seen from equation (1) that moment is proportional to the square of span in bending. Thus, a longer span with no change in rib depth, reinforcement or structural system will impart more than a proportional increase in flexural demand. Negative bending moments can also develop in continuous slabs on internal supports. For a preliminary design the applied area load can be transformed into a line load on a single rib by using its tributary width[11]:

$$w = q_s + w_{rib} \quad (2)$$

where q is the area load measured in kN/m^2 , s is the rib spacing in m , and w_{rib} is the self-weight of the rib, portion not included in q , in kN/m . Load definition shall not account for double the weight of: the Loff or other Components. The line load calculation is also based on the premise that the chosen tributary-width method is suitable for the slab in question.

3.2 Shear resistance and failure mechanisms

Concentration shear force is especially relevant in ribs as they have relatively thin webs in comparison with the total slab width. Point loads and supports reactions may induce high shear stresses at the ends of the ribs. When the required shear strength is not provided, diagonal cracking can appear and cause to brittle collapse. The moment of resistance of a slab should be calculated with a flexural resistance to be considered together with the design shear force. Shear capacity may be function of concrete strength, d , ρ_l , and ρ_t , depending on the controlling code and structural system. Stirrups should be provided if the calculated shear demand is greater than the shear capacity of concrete and other allowed contributions. Common failure modes are[12]

- Flexural failure with yielding of the longitudinal reinforcements
- Diagonal tension failure as a result shear overloading
- Compression failure of concrete in a highly loaded area

• .Anchorage or bond failure if the reinforcement is not properly developed .A ductile flexural response is typically more desirable than an abrupt shear failure. Hence, the ribbed slab design requires the detailing and validation of the dominant failure mechanisms ,which is the crux of this paper.

3.3 Deflection and cracking

Serviceability considerations, such as deflection and cracking, may control the design of thin ribbed slabs, even when their strength is sufficient. Instantaneous deflection is a function of flexural stiffness, span, load, and cracking width. Creep, shrinkage, and long-term loading also influence late deflections. Long-term deflection is also influenced by sustained loading, of course. For a simplified model of a simply supported beam with constant flexural rigidity and a uniform load distribution, the peak elastic deflection is[13]:

$$\delta_{\max} = \frac{5wL^4}{384EI} \quad (3)$$

where $\delta_{\max}$ is the maximum vertical deflection, E is the elastic modulus, and I is the second moment of area of the section.

It can be seen from Eq (3) that the deflection is very sensitive to the span length (i.e., it is proportional to the fourth power of the span) if the above assumptions hold. Nevertheless, real reinforced concrete ribs may crack, have a lower effective stiffness and deform over time. Therefore, this equation is more appropriate to understand the fundamental behavior; it is not a substitute for code-required deflection calculations for cracked reinforced concrete sections.

Table 1. Main structural performance characteristics of concrete ribbed slabs

Performance parameter	Main influencing factors	Engineering significance
Flexural strength	Rib depth, reinforcement area, concrete strength	Determines resistance to bending moments
Shear resistance	Web width, effective depth, concrete strength, stirrups	Controls resistance to diagonal cracking and shear failure
Deflection	Span, flexural stiffness, cracking, sustained load	Influences serviceability and floor usability
Crack development	Reinforcement distribution, concrete properties, loading	Affects durability, appearance, and stiffness
Vibration	Mass, stiffness, span, damping	Influences occupant comfort
Self-weight	Topping thickness, rib dimensions, void geometry	Affects loads transferred to supporting elements
Durability	Concrete cover, exposure, cracking, material quality	Influences service life and maintenance requirements

The results in Table 1 show that the behavior of ribbed slab cannot be predicted by a single parameter. A minimum mass configuration is not in general the best solution in terms of

vibration response or long-term serviceability. Hence, a compromise in absolute strength, stiffness, durability and cost is required in structural design.

4. Design Methodologies for Concrete Ribbed Slabs

The analysis and design of ribbed slabs involves structural analysis, cross-sectional design, reinforcement detailing and serviceability verification. The choice of method depends on the slab configuration, span-to-depth ratio, loading, continuity and relevant design code.

4.1 Conventional analytical design

Standard practice design procedures apply traditional bending theory from mechanics of materials to determine the moment-curvature relationships, bending moment diagrams, shear force diagrams, deflections, and reinforcement areas. For one-way ribbed slabs, each rib can be treated as a beam with a width equal to its tributary width, on the condition that this simplification does not compromise the structural performance. The concrete rib and topping can be considered as a T-section if the composite action is recognized. In positive bending, the topping usually serves as the compression flange, and the longitudinal reinforcement is in tension. In negative bending over continuous supports (negative moment), the compression and tension zones could interchange and special reinforcing will be required close to the top surface. In the case of a simplified singly reinforced rectangular beam, the nominal flexural capacity may be expressed as [14]:

$$M_n = A_s f_y \left(d - \frac{a}{2} \right) \quad (4)$$

where M_n is the nominal flexural resistance, A_s is the area of tensile reinforcement, f_y is the specified yield strength of the reinforcement, d is the effective depth, and a is the depth of the equivalent rectangular compression block.

This expression is valid only when the assumptions of the chosen section model are fulfilled. For a T-shaped section of a ribbed slab, the position of the compression block and the effective width of the flange must be determined in accordance with the pertinent design rules. The design strength shall also be proportional to the relevant strength-reduction or partial safety factors.

4.2 Finite element analysis

Finite element analysis (FEA) is commonly used to study ribbed slabs, particularly when their shape, support conditions, loading, or material response is complex. The level of detail can vary: the slab topping may be represented by shell elements, the ribs by beam elements, or the whole structure by three-dimensional solid elements. Simpler models take less computing time and make it easier to compare different design options. However, they may miss details such as local stress concentrations, crack development, and how the topping and ribs interact. To produce reliable results, the model needs suitable material data, support conditions, loading, and mesh size. For nonlinear analysis, the concrete and reinforcement behavior also need to be represented carefully. Before relying on the results to guide design decisions, the model should be checked against test data or sound, independently verified calculations. [15]




Figure 3 . General analytical and numerical design workflow

1. Structural system definition Span ,rib spacing, supports, materials and design code
 - 2 .Calculate loads Dead load, finishes, partitions and live loads
 - 3.Calculate the structural reaction Bending moments, shear forces ,support reactions and displacements
 - 4.Cross-section design Flexural strength, shear capacity and the amount of reinforcement
 5. Assess performance Deflection ,cracking, vibration, service life and fire resistance.
 6. Validate and optimize Compliance with the code, model validation and material efficiency
- Figure 2. A generalized procedure for the design and verification of concrete ribbed slabs .The process of Figure 2 underlines that the structural design is iterative. If a section does not pass a strength or serviceability check, the engineer may need to alter the ribs dimensions, the reinforcement layout, the slab thickness or the structural configuration and perform the analysis again.

4.3 Structural optimization and material efficiency

Optimization seeks to find the slab layout that meets the structural requirements with minimum material use, construction cost, or environmental impact. Design variables commonly considered are rib spacing (spacing between two consecutive ribs), rib depth, rib width, topping thickness

and area of reinforcement. The saving in concrete can be calculated as the difference between the volume of concrete in the ribbed slab and that for a solid slab of equal depth over the same floor area. A general formula for the percentage reduction is in general terms.:

$$RV = \frac{V_s - V_r}{V_s} \times 100\% \quad (5)$$

where R_V is the percentage reduction in concrete volume, V_s is the concrete volume of the reference solid slab, and V_r is the concrete volume of the ribbed slab over the same area.

A positive value means the ribbed design uses less concrete than the reference slab, provided both systems cover the same floor area and are measured within the same boundaries. However, using less concrete doesn't necessarily make the design cheaper or more sustainable overall. Reinforcement, formwork, labor, and construction difficulty also affect cost and environmental impact[16].

Table 2. Comparison of design and analysis methodologies

Methodology	Principal advantages	Main limitations	Suitable application
Classical beam analysis	Simple, transparent, and computationally efficient	Relies on idealized structural behavior	Preliminary design of regular one-way slabs
Equivalent T-beam method	Represents flange contribution to flexural resistance	Requires appropriate effective flange assumptions	Cross-sectional strength calculations
Grillage analysis	Represents load distribution through intersecting members	Results depend on member idealization and stiffness assumptions	Two-way ribbed floor systems
Linear finite element analysis	Efficient assessment of complex geometry and load distribution	Does not directly capture nonlinear cracking and failure	Elastic analysis and preliminary design
Nonlinear finite element analysis	Can represent cracking, material nonlinearity, and post-cracking response	Requires careful calibration and greater computational effort	Advanced performance assessment
Experimental testing	Provides direct evidence of structural behavior	May be costly and limited to tested configurations	Model validation and research investigations

Table 2 shows that no single method is universally superior. Classical methods remain useful for routine design and independent checks, while numerical and experimental approaches become more important when the structural response is complex or when new materials and configurations are investigated.

5. Recent Research Developments

5.1 Lightweight and fiber-reinforced concrete

The goal of the study for lightweight concrete is to reduce the dead load of structure and ensure sufficient strength and stiffness for safe service performance. Reduced density can decrease the dead loads and the loads on the supporting elements. Yet lightweight concrete may have a different modulus of elasticity, tensile behavior and cracking pattern than normal concrete and, therefore, these variations have to be accounted for in the analysis. Fiber-reinforced concrete is also of interest as fibers may enhance crack management and post-crack performance. The performance of a fiber depends on its material, shape, volume fraction, and orientation. Experimental testing is crucially important to see whether improvements in tensile behaviour translate into reliable design advantages for ribbed slab systems.

5.2 Dynamic performance and vibration

With the slenderization of floor systems, vibration performance might become a relevant design factor. Natural frequency and damping affect the response of a floor to dynamic load induced by occupants, machines, or other sources. Medeiros et al. (2024) studied the dynamic properties of R.C. one-way ribbed slabs by analytical, experimental and numerical techniques. This class of hybrid approach is beneficial in that it enables numerical predictions to be validated with measured structural response. Vibration evaluation will need to be coordinated with strength and deflection evaluations, especially for floors with long spans or sensitive occupancies.

5.3 Fire resistance

Exposure to fire can lower the strength and modulus of concrete and reinforcement and can result in high thermal gradients even through the depth of a slab. In particular, ribbed profiles need special care as their geometry, concrete layer and reinforcement arrangement influence the heating rate and the structural behaviour at elevated temperature. Thermal numerical simulations can be useful to predict the temperature fields in the ribs and the topping. Reliable fire design must however also account for structural restraint, the level of load in fire, material degradation, and the provisions in the relevant code. A thermal model by itself does not determine the fire resistance of the entire floor system unless the corresponding structural response is also properly analyzed.

5.4 Sustainability and life-cycle assessment

The smaller concrete volume of ribbed slabs can provide environmental benefits, especially if it results in a reduction of the overall material demand of a building. However, an impactful evaluation of sustainability would have to encompass all the life-cycle stages, such as raw material extraction, reinforcement, formwork, construction, maintenance and service life. In future work, structural optimization could be coupled with life-cycle assessment to assess if reductions in concrete usage are still favoured when other materials and construction procedures are considered. Such investigations should be conducted on systems with equal structural capacity and serviceability rather than on material quantities on their own.

6. Illustrative Structural Calculations

As a preliminary example, take a one-way ribbed slab spanning 5.0 m, with ribs spaced 0.60 m apart. Assume the area load is 6.0 kN/m², including the topping and other distributed loads, and that each rib adds 0.8 kN/m of self-weight. The line load on a single rib can then be calculated using Equation (2):

$$w=(6.0)(0.60)+0.8=4.4 \text{ kN/m}$$

For a simply supported rib under this uniformly distributed load, Equation (1) gives:

$$M_{\max} = \frac{(4.4)(5.0)^2}{8} = 13.75 \text{ kN}$$

The corresponding maximum support shear force is:

$$V_{\max} = \frac{wL}{2} \quad (6)$$

Substituting the assumed values gives:

$$V_{\max} = \frac{(4.4)(5.0)}{2} = 11.0$$

These are tentative estimates of internal forces, not results from a finalized structural design. The size of the ribs, the strength of the concrete, the amount of reinforcement, the type of bearing, and the load combinations considered must be known to check the flexural and shear strength

Table 3. Illustrative design inputs and calculated responses

Parameter	Symbol	Illustrative value
Span length	L	5.0 m
Rib spacing	s	0.60 m
Area load	q	6.0 kN/m ²
Additional rib self-weight	w_{rib}	0.8 kN/m
Calculated line load	www	4.4 kN/m
Maximum bending moment	$M_{\max}$	13.75 kN·m
Maximum support shear	$V_{\max}$	11.0 kN

For instance, the floor area load is converted to the load on a single rib and is then applied to the estimation of the principal internal forces. In the end, the engineer needs to check load definitions, relevant load combinations, continuity effects, and design-code requirements, then decide on the final section and the reinforcement.

7. Research Gaps and Future Research Directions

Despite great advances in design and analysis of concrete ribbed slabs, there are still a few matters that require attention. The following gaps in the literature are especially pertinent to the future experimental and numerical efforts.

Table 4. Research gaps and proposed future investigations

Research gap	Limitation or unresolved issue	Recommended research direction
Flexural and shear interaction	Simplified calculations may not capture all local effects	Conduct experimental tests supported by validated nonlinear models
Long-term deflection	Creep, shrinkage, and cracking complicate prediction	Develop and validate long-term response models
Alternative concrete materials	Material benefits may vary with rib geometry and reinforcement	Compare conventional, lightweight, and fiber-reinforced concrete
Dynamic performance	Frequency and damping predictions depend on stiffness and boundary conditions	Combine modal testing with numerical analysis
Fire resistance	Temperature distribution alone does not establish structural capacity	Couple thermal analysis with structural response calculations
Sustainability	Reduced concrete volume does not represent the entire environmental impact	Integrate life-cycle assessment with structural optimization
Design-code comparisons	Different provisions may lead to different design outcomes	Compare code-based predictions against common benchmark tests

The table highlights ways to make design methods more dependable and evaluate ribbed slabs more fully. One promising approach is to pair physical testing with computer simulations and optimization. This would help researchers understand how different design dimensions affect strength, deflection, material use, and environmental impact.

8. Parametric Analysis and Performance Evaluation

The influence of rib spacing, rib depth, topping thickness, concrete strength, and reinforcement ratio on the behavior of a ribbed slab can be studied by a parametric study. The parameters need to be altered in a controlled manner, i.e. the other variables need to be held constant, so as to observe the direct and interactive effects. For instance, a decrease in rib spacing could enhance load distribution, potentially change floor system stiffness, and result in an increase in the number of ribs – and in formwork and reinforcing needs. Increasing the rib depth may enhance flexural stiffness but it may impact the floor-to-floor height and the architectural coordination. Such trade-offs suggest that the optimal solution must be obtained through a combination of structural analysis and practical considerations of construction. A simplified performance measure to represent the comparison of a structural demand with capacity is:

$$\eta = \frac{S_d}{R_d} \quad (7)$$

where η is the demand-to-resistance ratio, SdS is the design action effect, and Rd is the corresponding design resistance, expressed on a consistent basis.

If the ratio is smaller than unity, it means that the considered strength check is fulfilled satisfied the the demand-to-resistance ratio. But this does not imply that the whole slab is safe: all the pertinent strength checks, serviceability criteria, detailing regulations and any other relevant limit states must be checked .For a first estimation of structural forms, material efficiency can be also defined as:

$$\xi = \frac{Rd}{V_c} \quad (8)$$

where ξ is a simplified resistance-per-unit-concrete-volume indicator and V_c is the concrete volume associated with the member or slab system.

Larger value of ξ represents larger design resistance under given definition per volume of concrete. However, this index ignores the consumption of reinforcement, the cost of construction, the deflection, the service life and the environmental effect .So it can be considered a part of the jigsaw in evaluating overall performance.

9. Conclusions

The concrete ribbed slab is a successful type of reinforced concrete floor system that can reduce the self-weight and concrete usage with adequate flexural resistance when well designed. Their structural capacity is a function of the interaction between the concrete topping, ribs, reinforcement, the applied load conditions, and the substructure. Then Developable design of reinforced concrete beams should consider key design parameters including bending strength, shear strength, deflection, cracking and vibration .Traditional analytical techniques give a good basis for general, day to day structural design and finite element modeling permits a more detailed study of complex geometry, non-linear material behavior and stress distribution. Experimental testing continues to be crucial for the validation of numerical results, particularly when novel materials or atypical configurations are taken into account .For ribbed slab engineering, recent developments in the literature cover lightweight and fiber reinforced concrete, dynamic performance, fire resistance, and so on. However, additional efforts are still needed to draw consistent correlations among geometry, mechanical behavior, long term performance and environmental exposure .Research should be directed towards combining code-based design, experimentally validated numerical models, and life-cycle assessment. This holistic methodology can be used to enable safer, cost-effective and more sustainable concrete ribbed slab systems.

References

1. Y. Y. Mo and A. C. Galeb, “Key effects on the structural behavior of fiber-reinforced lightweight concrete-ribbed slabs: A review,” *Open Engineering*, vol. 14, no. 1, pp. 325–333, 2024. [Online]. Available: <https://doi.org/10.1515/eng-2024-0054>

2. P. V. Sacramento, M. S. Picanço, and D. C. Oliveira, “Reinforced concrete ribbed slabs with wide-beam,” *Revista IBRACON de Estruturas e Materiais*, vol. 11, no. 5, 2018. [Online]. Available: <https://doi.org/10.1590/S1983-41952018000500005>
3. A. A. Sulaibi and D. N. H. Al-Amiery, “Analysis and parametric study of reinforced concrete two-way ribbed slabs by using ANSYS,” *American Scientific Research Journal for Engineering, Technology, and Sciences*. [Online]. Available: https://asrjetsjournal.org/American_Scientific_Journal/article/view/2812
4. “Experimental and numerical evaluation of RC ribbed slabs in fire conditions,” *Structures*, vol. 51, pp. 747–759, May 2023. [Online]. Available: <https://doi.org/10.1016/j.istruc.2023.03.057>
5. S. R. Jasim and H. M. J. Al-Khafaji, “Improve the flexural behavior of one-way ribbed slab by using CFRP sheet,” *Tikrit Journal of Engineering Sciences*, 2024. [Online]. Available: <https://doi.org/10.25130/tjes.31.2.25>
6. M. Huber et al., “Structural design and testing of material optimized ribbed RC slabs with 3D printed formwork,” *Structural Concrete*, vol. 24, no. 2, pp. 1932–1955, 2023. [Online]. Available: <https://doi.org/10.1002/suco.202200633>
7. I. da S. Medeiros, H. T. Lima, D. M. de Lima, L. E. de M. Alas, and P. A. López-Yáñez, “Dynamic parameters in reinforced concrete one-way ribbed slabs: Theoretical approach, experimental investigation and numerical modeling,” *Engineering Structures*, vol. 314, Art. no. 118350, Sep. 2024. [Online]. Available: <https://doi.org/10.1016/j.engstruct.2024.118350>
8. E. Çelebi and O. Kırtel, “Seismic performance of reinforced concrete framed buildings with ribbed slabs at the affected region by 2023 Kahramanmaraş earthquakes,” *Bulletin of Earthquake Engineering*, vol. 23, pp. 3623–3646, 2025. [Online]. Available: <https://doi.org/10.1007/s10518-025-02191-0>
9. “Simplified calculation model and finite-element analysis of frame-supported ribbed-grid composite slab structure,” *KSCE Journal of Civil Engineering*, vol. 22, no. 9, pp. 3383–3394, Sep. 2018. [Online]. Available: <https://doi.org/10.1007/s12205-017-0457-5>
10. ACI Committee 318, *Building Code Requirements for Structural Concrete (ACI 318-19) and Commentary (ACI 318R-19)*. Farmington Hills, MI, USA: American Concrete Institute, 2019.
11. European Committee for Standardization, *Eurocode 2: Design of Concrete Structures—Part 1-1: General Rules and Rules for Buildings*, EN 1992-1-1. Brussels, Belgium: CEN, 2004.
12. Y. Yahya and A. C. Galeb, “Key effects on the structural behavior of fiber-reinforced lightweight concrete-ribbed slabs: A review,” *Open Engineering*, vol. 14, 2024. <https://doi.org/10.1515/eng-2024-0054>.
13. K. E. Nikitin and O. A. Kirsanov, “Comparative study of finite element methods of calculation of ribbed reinforced concrete floors,” *Structural Mechanics of Engineering Constructions and Buildings*, vol. 18, no. 3, pp. 242–254, 2022. <https://doi.org/10.22363/1815-5235-2022-18-3-242-254>.
14. A. V. Tomashevskiy, “Problems of computer structural analysis and reinforcement calculation techniques of reinforced concrete ribbed slabs,” *Building Production*, no. 72, pp. 39–45, 2023. <https://doi.org/10.36750/2524-2555.72.39-45>.

15. I. da S. Medeiros et al., “Dynamic parameters in reinforced concrete one-way ribbed slabs: Theoretical approach, experimental investigation and numerical modeling,” *Engineering Structures*, vol. 314, article 118350, 2024. <https://doi.org/10.1016/j.engstruct.2024.118350>.
16. American Concrete Institute, *Building Code Requirements for Structural Concrete (ACI 318-19) and Commentary*. Farmington Hills, MI, USA: ACI, 2019.